

MODEL LC-191002D

- **2D Desktop Barcode Scanner**
- **Easy to Use**
- **Plug and Play Facility**
- **Supports Multiple Languages**

A 2D desktop barcode scanner LC-191002D is characterized by light weight, remarkable performance without pause thus assuring proper work efficiency.

Stylish and exquisite in appearance, LC-191002D barcode scanner comes with stable working solution bringing a lot of convenience to the user. For easy operations these barcode scanners can be used in all barcode scanning situations.



- 32bit CPU, super decoding ability, support multiple languages.
- Plug & play, no need for any driver or software. Easy installation with USB cable.
- Extra-large scanning angle easily identifies screen code.
- Desktop hand-free design, auto sense, when the scanner reaches the barcode it automatically decodes the barcode.

Features

- Desktop mounted, easy to use.
- 32Bit CPU, Super decoding ability, support multiple languages.
- Wired scanning platform improves the working efficiency.
- Compatible with Systems - Windows, Mac OS, POS Cash Register, Linux.
- Plug and play facility, there is no need for any driver or software.
- Easy installation with USB cable.
- Extra-Large scanning angle that easily identifies screen code
- Super decoding ability, fast to scan both printed and mobile phone screen 1D/2D barcodes.
- Desktop Hand-Free Design with auto sense, i.e., when the scanner reaches the barcode it will automatically decode the barcode.
- Application Fields: Supermarket, Retail, Warehouse, Logistics, Library, Medical, etc.

Specifications

Product Specification: LC-191002D 2D Desktop Barcode Scanner

Scanner Parameters:

Optical Resolution	640*480
Lighting Source	Red LED Supplement
Scanning Speed	2200 times/s
Scanning Angle	Rotate Roll:0-360 degree, tilt pitch: ±65 degrees, deflect SKEW: ±65 degrees
Sweeping Barcode Type	paper, thin film medium one-dimensional; mobile phone, flat screen, etc.
Printing Contrast	20%
Error Rate	≤1/2,000,000
Interface Type	USB:HID Keyboard(default mode), USB virtual serial port
IP Level	up to IP5X standard
Prompt Mode	buzzer sound prompt and green light prompt
Decoding Capability	1D:Code 39, Full ASCII Code 39, Code 32, Code 128, Code 93,Code 11, Codabar/NW7, All UPC/EAN/JAN code (EAN-13,EAN-8, UPC-A, UPC-E, EAN-128), Interleave 2 of 5, STD 2of 5, Industrial 2 of 5, matrix 2 of 5, Chinese Postage Code, IATA, MSI/PLESSY, Italian Pharmacy Code, Industrial 2 of 5,BC-412, etc. 2D:QR Code, Data Matrix, PDF417, Aztec code, Maxicode, etc.

Electrical Parameters

Electric Voltage	5V DC
Working Current	390mA(Max.),220mA(Typical)
Optical Safety Certification	ICE42471, IEC60950
Electromagnetic Compatibility	EN55022, EN55024

Mechanical Parameters

Size	110mm*150mm*110mm
Cable Length	2m
Weight	450g

Environmental Parameters

Working Temperature	-20°C~60°C
Storage Temperature	-20°C~70°C
Working Humidity	0%~80%
Drop Test	2m

RIYADH

tel: +966-11-4657722
fax: +966-11-4661323

JEDDAH

tel: +966-12-6736677
fax: +966-12-6554516

KHOBAR

tel: +966-13-8311344
fax: +966-13-8986549

