



Arm Drop Barriers MTZ - 6618 Series

idPoint™

Models

- MTZ 6618S Single Side Arm Drop Barrier
- MTZ 6618D Double Side Arm Drop Barrier

Features

- Elegant stylish design.
- High quality stainless steel corrosion resistant body.
- Alarm against reverse direction passing.
- Can be use automatic identification system, access control and attendance check, etc.
- Bidirectional indicating windows.
- Invalid entering alarm.
- LED gate direction indicator.
- Audible sound prompt and information display optional.
- Counting Function.
- Manually handle to open/close gate.
- state of the art external electronics.
- Uses latest brushless motor technology for smoothless operation and Long-life.



Specification

Type	Single flap	Double flap
Power Consumption	50W	100W
Housing Size	1400*160*950mm	
Housing Material	1.5--2mm, 304# stainless steel, Corrosion resistant	
Channel Width	≤1150mm	
Transit Speed	40 persons/min	
Communication Interface	RS485	
Input Signal Optional	Dc 12V level signal or DC 12V pulse dignal	
Gate Open in the Case of Power Failure	Optional	
Working Temperature	-30°C to 70°C	
Working Environments	Indoor, Outdoor(In Shelter)	



Riyadh

Call: +966-11-4657722

Fax: +966-11-4661323

Jeddah

Call: +966-12-6736677

Fax: +966-12-6554516

Khobar

Call: +966-13-8644070

Fax: +966-13-8986549